

## **NTG Motor Services Limited**

282 - 284 Bramford Road Ipswich Suffolk IP1 4AY

 Tel: ++44 (0)1473 - 406031 & 406032

 Fax: ++44 (0)1473 - 743133
 Email: sales@mgbits.com

 www.mgbits.com
 www.bmcfarina.com

Directors: M.Green P.Banyard Company Reg.No. 1262476 V.A.T.Reg. No. 289 5422 17

Each conversion kit contains all the parts necessary to adapt a Ford Sierra (Type 9) 5-speed gearbox to the MG car and engine. Gearboxes can be supplied in standard ratio or a variety of alternative ratios to suit the vehicle power and purpose. The kits require little or no vehicle modification and are reversible. They are sold all over the world. 500+ sold to date.

## MG TF 5 Speed Gearbox Conversion

The MG T type 5 speed gearbox conversion kit has been developed as a further successor to the popular MGA and MGB conversions designed and developed by Hi-Gear. The kit is aimed at T type owners who really want to use their cars on modern roads including motorways and who do not want to be confined to secondary roads.

The conversion transforms the car into a usable cruiser. Other benefits include improved fuel consumption less driver and passenger fatigue less vibration longer engine life and fewer broken crankshafts! Motorway cruising is enhanced by the fifth gear.

The conversion adapts a Ford Sierra Type 9 gearbox (5 speed 1.6L & 1.8L: 1982-91 & 2.0L: 1982-87) to the XPAG and XPEG engines.

To enable the Ford gearbox to be fitted to the vehicle the engine has to be moved approximately 10mm forward. The kit has all the parts to enable this to be achieved safely and reliably together with all fasteners and fitting instructions for the competent owner to fit.

## The Type 9 Ford gearbox is not part of the kit but is either supplied by the owner or we can supply a fully reconditioned gearbox (See Part number E250)

The vehicle speedometer will need calibrating. Several companies are able to do this. Instructions on how to measure the vehicle speedometer characteristics for re-calibration are included together with the details of a suitable company to do the work.

The Kit Comprises:

- Cast aluminium Bell Housing.
- Gasket Bell Housing to gearbox.
- Spigot bush.
- Rear rubber gearbox mounting.
- Modified front rubber engine mounting.
- New gearbox support crossmember.
- Two crossmember side supports/lockplates.

- Engine mounting packing plate.
- Exhaust support bracket.
- Engine torque reaction bracket/bolt.
- Two floor rail support brackets.
- Gear lever assembly (chrome)
- Clutch plate (for 7<sup>1</sup>/<sub>4</sub>" or 8" pressure plate).
- Speedometer cable/circlip.





## **NTG Motor Services Limited**

282 - 284 Bramford Road Ipswich Suffolk IP1 4AY

 Tel: ++44 (0)1473 - 406031 & 406032

 Fax: ++44 (0)1473 - 743133
 Email: sales@mgbits.com

 www.mgbits.com
 www.bmcfarina.com

Directors: M.Green P.Banyard Company Reg.No. 1262476 V.A.T.Reg. No. 289 5422 17

- Brake pipe (RHD only).
- Fan spacer + bolts.
- Modified front wing tie bar.
- Propshaft.

- Gearbox cover in moulded ABS.
- All bolts and fasteners.
- Detailed fitting instructions.
- Loctite.

The Bell Housing is cast in LM25 high strength heat treated aluminium alloy and is robustly constructed. The standard MG 7<sup>1</sup>/<sub>4</sub>" or 8" clutch cover is re-used. The standard clutch release bearing and cross shaft system are all retained. The gear lever sits in the same place as usual so the conversion is not easily detectable.

The gearbox supporting chassis tube is retained. The brackets welded to the tube have a small piece removed but will still be able to be re-used if needed.

TF axle ratio 4.875:1
4th gear 15.16 mph/1000 rpm
5th gear 18.48 mph/1000 rpm
70 mph 4617 rpm (4th) ->3787 rpm (5th)
TF 1500 axle ratio 4.55:1
4th gear 16.22 mph/1000 rpm
5th gear 19.78 mph/1000 rpm
70 mph 4315 rpm (4th) ->3538 rpm (5th)
The propeller shaft provided in the kit is to the original manufacturer's specification:
Torque: 570 Nm 422lbft (short duration) MAXIMUM
Speed: 7000 Rpm MAXIMUM.

This corresponds to 5740 engine rpm in fifth gear (ratio 0.82:1) and 7000 engine rpm in fourth gear (ratio 1:1).

